

METHOD AND DEVICE FOR EXECUTING METHOD STEPS5 Background of the Invention:Field of the Invention:

10 The invention relates to a method for processing method steps, whereby an output signal is output in one method step. The invention also pertains to the processing of method steps with a control device that outputs an output signal.

15 In the controlling of printing machines, for example, method steps are automatically executed in series by a control apparatus. The method steps comprise for example the controlling of a printing unit or the controlling of a print cylinder. Moreover, method steps are preferably provided with which a correct functioning of the controlled machine is monitored. If the control apparatus recognizes a malfunction, an output signal is produced and outputted via an output unit.

20 In addition, programs for producing a program flow are known wherein method steps are provided that monitor a correct execution of the program flow. If a program error is recognized in a method step, the error is output via an output unit.

25

Summary of the Invention:

The object of the present invention is to provide a method and device for executing method steps which overcome the above-noted deficiencies and disadvantages of the prior art devices and methods of this general kind, and which provided for a greater degree of flexibility.

With the above and other objects in view there is provided, in accordance with the invention, a method of executing method steps, which comprises:

checking whether an output mode is switched on; and

producing an output signal in a method step and outputting the output signal only if the output mode is switched on.

In other words, an output signal is outputted only if an output mode is switched on. The use of an output mode offers the advantage that output signals are output only when the output mode is switched on. If the output mode is not switched on, the output signal is produced but is not output.

In accordance with an added feature of the invention, the method steps are divided into modules, and the method comprises changing from one module to another module during the execution of the method steps, and wherein the output

signal comprises an identifier indicating in which module the output signal was produced.

5 In accordance with an additional feature of the invention, the method steps are executed in a plurality of devices, and the output signal is generated with an identifier indicating the device in which the output signal was produced.

10 In accordance with another feature of the invention, the method steps are stored in a storage device, and the method comprises reading out the method steps from the storage device and executed the method steps, and wherein the output signal comprises an identifier indicating where the method step is stored that produced the output signal.

15 In accordance with a further feature of the invention, the output signal comprises an identifier indicating in which method step the output signal was produced.

20 In accordance with again an added feature of the invention, the output mode is one of a plurality of output modes, and the method comprises checking which output mode is set, and wherein the output signal comprises an identifier indicating to which output mode the output signal belongs, and wherein
25 only the output signals belonging to the set output mode are outputted.

In accordance with again an additional feature of the invention, the output signal is output via an output unit as a signal selected from the group consisting of optical and
5 acoustic signals.

In accordance with again another feature of the invention, the output signal is stored in a storage device, together with an indication of a time at which the output signal was stored.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221

In accordance with yet an additional feature of the invention, the output signal includes an identifier indicating at which method step the output signal was produced.

- 5 In accordance with yet another feature of the invention, at least one of the first and second control apparatus executes method steps in the form of program modules, and the output signal comprises an identifier indicating the module in which the output signal was produced.

10

In accordance with yet a further feature of the invention, the method steps are stored in a storage device, and

15

at least one of the first and second control apparatus is configured to read out the method steps for the execution from the storage device; and

20

the output signal comprises an identifier indicating a location at which the method steps are stored in the storage device. The location is identified via a memory address and/or a data filename.

25

In accordance with a concomitant feature of the invention, input means are configured to enable selective switching on and switching off of the output mode even during the execution of the method steps.

Additional advantageous developments of the invention are indicated in the dependent claims. In preferred specific embodiments of the invention, the output signal comprises
5 identifiers that for example indicate wherein module, wherein device, or wherein method step the output signal was produced. In further advantageous specific embodiments, the output signal comprises an identifier that indicates where the method step is stored that resulted in the production of the output
10 signal.

In addition, various output modes are preferably provided wherein predetermined types of output signals are outputted, and the output signal preferably comprises an identifier that
15 indicates which output mode is switched on.

In a further preferred specific embodiment, the output signal is stored in a storage device with an indication of the time at which the storing took place. This specific embodiment
20 enables a statement concerning the time of occurrence of the output signal.

Other features which are considered as characteristic for the invention are set forth in the appended claims.

Although the invention is illustrated and described herein as embodied in a method and device for executing method steps, it is nevertheless not intended to be limited to the details shown, since various modifications and structural changes may be made therein without departing from the spirit of the invention and within the scope and range of equivalents of the claims.

The construction and method of operation of the invention, however, together with additional objects and advantages thereof will be best understood from the following description of specific embodiments when read in connection with the accompanying drawings.

Brief Description of the Drawings:

Fig. 1 is a block diagram showing a device for executing method steps;

Fig. 2 is a schematic block diagram of a network of devices for executing method steps;

Fig. 3 is a flow diagram; and

Fig. 4 shows two output signals.

Description of the Preferred Embodiments:

Referring now to the figures of the drawing in detail and first, particularly, to Fig. 1 thereof, there is seen a device for controlling a first printing machine 7. Certain method
5 steps are executed for controlling the first printing machine 7. The method steps are, by way of example, realized in the form of hardware and/or in the form of computer programs.

The device comprises a control apparatus 2, which is connected with an input unit 1 via an input line 8, and with an output
10 unit 4 via an output line 9, and with a storage device 3 via a data line 10, and with a second control apparatus 5 via a first interface 11, and with first printing machine 7 via control lines 12. Instead of the first printing machine 7,
15 the control apparatus 2 can be connected with a controlling element or an actuator. In other words, the invention is not limited to the controlling of a first printing machine 7, but rather is suitable for controlling of arbitrary types of
controlling elements, controlled elements, and/or machines.

20 The second control apparatus 5 is connected with a second storage device 6 via a second data line 13. In addition, second control apparatus 5 is connected via a second input line 14 with a second input unit 15 and, via a second output
25 line 16, with a second output unit 17. In addition, a second printing machine 19 is provided, with which the second control

apparatus 5 is connected via second control lines 18. Instead of the second printing machine 19, a controlling element or another machine can be provided that is controlled by the second control apparatus 5. In a preferred specific embodiment, the second control apparatus 5 is connected with the first printing machine 7 via third control lines 20. In this specific embodiment, the first printing machine 7 is preferably controlled in various functions and/or simultaneously by the first and second control apparatus 2, 5.

The second control apparatus 5, with second input unit 15, second output unit 17, second storage device 6, and second printing machine 19, represents a subsystem that is monitored and/or controlled by the first control apparatus 2. The first control apparatus 2 thus represents a master computer that monitors and/or controls the second control apparatus 5, which is fashioned as a slave computer.

Referring now to Fig. 2, there is shown, schematically, a main system 28 with the first control apparatus 2 as a master computer, connected via an interface 11 with a first subsystem 21. The second control apparatus 5 is arranged in the first subsystem 21. In addition, main system 28 is connected, via additional interfaces 22, 23, with a second and third subsystem 24, 25. Second and third subsystem each comprise a control apparatus with input and output and storage device.

The design of a device for processing method steps in the form of a main system 28 and a plurality of subsystems 21, 24, 25 has the advantage that tasks are executed in parallel by subsystems, and the subsystems are monitored and controlled by the main system. In this way, a rapid execution of tasks is possible, since the tasks are executed in parallel. In addition, through the arrangement of the main system good coordination is enabled, for example with reference to the workload of the subsystems. In addition, the use of a plurality of subsystems has the advantage that one subsystem can be provided as a substitute system for another subsystem, whereby the substitute system takes over the tasks of the other subsystem when the latter has failed or is no longer functioning correctly.

At the same time, due to the subsystem structure it is difficult to have an overview concerning which subsystem executes method steps, and at which method step an output, in particular an errored output, is produced, and where the method step that produced an output command is stored.

In the following, the invention is explained in more detail on the basis of Figs. 1 and 2, in relation to the program flow of Fig. 3. Fig. 3 shows a program flow divided into a first module 26 and a second module 27. The first module 26

comprises method steps 30 to 90, and the second module 27 comprises method steps 100 to 150. The first module 26 is executed in the first control apparatus 2 in the main system 28, and the second module 27 is executed in the first subsystem 21 by the second control apparatus 5. The method steps of the first module 26 are stored in the first storage device 3 (program memory), and the method steps of the second module 27 are stored in the second storage device 6 (program memory). Likewise, data and data files that are used for the execution of the first module 26 are preferably stored in the first storage device 3, and data and data files that are used for the execution of the second module 27 are preferably stored in the second data storage device 6.

At program point 30, the first control apparatus 2 starts the program flow and carries out an initialization of the data and data files required for the execution of first module 26. At the following program point 35, the first control apparatus 2 writes to the first storage device 3, in a first list, that the first module 26 is being executed, and additionally writes the memory address x, y from which the first module 26 was read out, and writes the first storage device 3 as the memory location of the memory address. In addition, the first storage device 2 writes to the first list that the first module 26 is being executed by the main system 28.

Subsequently, at program point 38 the first control apparatus 2 executes method steps. These can for example consist in the calculation of control data for a first printing machine 7, or in the preparation of an image to be printed out via a first printing machine 7. However, other tasks can also be executed by first control apparatus 2, wherein, for example, data are acquired by the input unit 1 or control data are outputted to the first printing machine 7.

Subsequently, at program point 40 a branching takes place to program point 100 of second module 27. The branching at program point 40 can be conditional or unconditional. The branching to program point 100 means that first control apparatus 2 outputs a control command to second control apparatus 5 via first interface 11. After receiving the control command at program point 100, second control apparatus 5 begins to execute second program module 27. At program point 100, second control apparatus 5 writes to a second list of second storage device 6 that the execution of second module 27 was initiated by first control apparatus 5 at program point 20 of first module 26.

Subsequently, at the following program point 110 second control apparatus 5 stores, in a third list of second storage device 6, the information that second module 27 is being executed, and that second module 27 is being executed by first

subsystem 21, and that the data files wherein the method steps of second module 27 are stored are stored in second storage device 6 at memory address x, y.

5 Subsequently, at program point 120, second control apparatus 5 carries out predetermined method steps wherein, for example, an input is requested from second input unit 15, or a control parameter is calculated for controlling the second printing machine 19 and/or the first printing machine 7, or the second
10 printing machine 19 and/or the first printing machine 7 are controlled with control parameters.

In addition, at program point 122 an output command is produced for the outputting of an item of information. An
15 item of information is used for example to obtain an overview of the execution of the method steps. In a network, it is of interest to know which control apparatus executes, or makes use of, which method steps, modules, storage devices, etc.. An item of output information is thereby preferably stored in
20 a first output field of second data storage device 6, said information comprising for example one or more of the following: wherein module the output information was produced; that an item of output information is concerned; which system produced the output information; which output mode is
25 concerned; at which program step the output information was produced; wherein data file the program step is stored, and at

which memory address, and wherein storage device the data file is stored.

Subsequently, program step 125 is executed, wherein a correct functioning of the execution of the program steps of second module 27, or a correct functioning of first and second printing machine 7, 19 is monitored. If the monitoring of the execution of the method steps reveals that an error has occurred, an item of error information is stored in a second output field of second storage device 6. The item of error information includes at least one of the following: wherein module the output information was produced; which system produced the output information; which output mode is concerned; at which program step the output information was produced; wherein data file the program step is stored, and at which memory address, and wherein storage device the data file is stored; that an item of error information is concerned relating to the program flow of second module 27.

If the monitoring of the functioning of first or second printing machine 7, 19 reveals that a malfunction has occurred, then in second storage device 6 an item of output information is stored in a third output field, said information preferably including at least one of the following: wherein module the output information was produced; which system produced the output information; which output

mode is concerned; at which program step the output information was produced; wherein data file the program step is stored, and at which memory address, and wherein storage device the data file is stored; the fact that an error output is concerned relating to the first and/or the second printing machine 7, 19, according to the printing machine 7, 19 at which the error was recognized.

In the following program step 130, second control apparatus 5 checks whether the first, second, or third output field of second storage device 6 is occupied. If this is the case, branching takes place to program point 140. At program point 140 it is checked whether the information mode, the error mode for the program flow, or the error mode for the manner of functioning of first or second printing machine 7, 19 is switched on. In addition, for the three output modes there are stored in second storage device 6 three memory fields, which are occupied with the value 1 when the corresponding modes are switched on. A switching on of the modes takes place either via an input or, dependent on a condition, automatically via second control apparatus 5.

If the query at program point 140 yields the result that one of the three output mode is switched on, branching takes place to program point 145. At program point 145, the output

information is outputted via first or second output unit 4,
 17. Subsequently, branching takes place to program point 150.

If the query at program point 140 yields the result that none
 5 of the output modes are switched on, branching takes place
 directly to program point 150.

If the query at program point 130 yields the result that none
 of the output fields are occupied, branching takes place
 10 directly to program point 150.

At program point 150, additional method steps of second module
 27 are executed, and a control command is subsequently handed
 over to first control apparatus 2 via first interface 11.

15 According to the specific embodiment of second module 27, data
 and/or calculated values are also handed over to first control
 apparatus 2.

After receiving the control command, control apparatus 2
 20 further executes first module 26 at program point 40.
 Additional method steps are thereby executed corresponding to
 program point 18.

Program point 30 contains method steps that are executed by
 25 control apparatus 2 if at program point 20 branching does not

take place to program point 100. Program point 44 follows
after execution of program point 30.

After execution of the method steps, at program point 45 an
5 information output is produced, preferably dependent on a
predetermined event, and is stored by first control apparatus
2 in first storage device 3, in a first output field. The
information output preferably comprises at least one of the
following items of information: the information was produced
10 in first module 26; the information output was produced at
method step 45; the method step was executed by the main
system; an information output is concerned; wherein data file
the method step is stored that resulted in the information
output, and at which memory address of first storage device 3
15 the data file is stored.

Subsequently, program point 48 is executed, wherein a correct
functioning of the execution of the program steps of first
module 26, or a correct functioning of first and second
20 printing machine 7, 19, is monitored. If the monitoring of
the execution of the method steps reveals that an error has
occurred, an item of error information is stored in a second
output field of first storage device 3. The item of error
information includes at least one of the following: wherein
25 module the output information was produced; which system
produced the output information; which output mode is

concerned; at which program step the output information was produced; wherein data file the program step is stored, and at which memory address, and wherein storage device the data file is stored; the fact that an item of error information is
5 concerned relating to the program flow.

10 If the monitoring of the functioning of first or second
printing machine 7, 19 reveals that a malfunction has occurred, then in third storage device 3 an item of output
information is stored in a third output field. The item of
information preferably includes at least one of the following:
wherein module the output information was produced; which
system produced the output information; which output mode is
concerned; at which program step the output information was
15 produced; wherein data file the program step is stored, and at
which memory address, and wherein storage device the data file
is stored; the fact that an error output is concerned relating
to first and/or second printing machine 7, 19, according to
the printing machine 7, 19 at which the error was recognized.

20

At the following program point 50, the first control apparatus
2 checks whether one of the three output fields in the first
storage device 3 is occupied. If the query returns a
negative, branching takes place to program point 90.

25

If the check at program point 50 reveals that at least one of the three output fields is occupied, branching takes place to program point 60. At program point 60, first control apparatus 2 checks whether the output mode for an item of information, the output mode for an error message relating to the program flow, or the output mode for the error message relating to the functioning of first or second printing machine 7, 19 is switched on. For this purpose, in storage device 3 there are stored three memory fields, one memory field being allocated respectively to one of the three modes of information. If an output mode is switched on, the corresponding memory field is occupied with the value 1.

If the query at program point 60 reveals that at least one of the three output modes is switched on, branching takes place to program point 70. If the query at program point 60 reveals that none of the three output modes is switched on, branching takes place directly to program point 90.

At program point 70, first control apparatus 2 outputs the information concerning first or second output unit 4, 17.

Subsequently, branching takes place to program point 90, at which for example first module 26 is terminated.

Fig. 4 shows a first item of output information A1 for an information output, whereby SI<1> indicates an identifier for first subsystem 21, MI<2> indicates an identifier for second module 27, MO<2> indicates an identifier for output mode Information, L<122> indicates an identifier for the method step 122 at which the output information was produced, and Info-Mode indicates a brief item of information. Preferably, the name of the data file Q and the memory location Q<x,y> of the data file wherein method step 122 is stored are also output.

The second output information A2 is an example of an error output, and has identifier SI<0> for main system 28, identifier MI<1> for first module 26, identifier MO<1> for the output mode 'error message,' identifier L<48> for indicating the method step at which the error information was produced, the word 'error mode' for the indication that an item of error information is concerned, and identifier Q as the name of the data file wherein method step 48 is stored, and Q<x,y> as the memory address at which the data file is stored in first storage device 3.

According to the specific embodiment, the outputs can contain a combination of the identifiers shown in Fig. 4.

In a preferred specific embodiment, the output modes can be switched on or switched off during the operation of first and second control apparatus 2, 5. In addition, the content of the outputs can be modified via a corresponding input via first or second input unit 1, 15. For example, different items of information can be determined for output for the various output modes.

In addition, via a corresponding input it can also be determined that items of information are not outputted, but rather are written into an output data file of first or second storage device 3, 6. The date and time of the storing are thereby preferably also stored during the storing of the output data file. In this way, the output information can be called at a later time, and, in addition, the time of the occurrence of the output information can be requested.

An advantage of the invention is that the type of outputting of an item of output information can be set in a flexible fashion, and, in addition, the output information includes an indication concerning at which method step, at which module, and at which main system or subsystem the output information was produced. In this way, despite a distributed execution of method steps, an overview is provided of the environment wherein the output information was produced.